Professional Light Meter ET-952

The light meter is designed to meet the measurement requirements of safety engineers, health, industrial safety offices and light quality control in various environments like factory, school, construction, etc.

FEATURES

- ◆Large backlit LCD display with 40-segment bar graph
- ◆Peak capture
- ◆Selectable measurement range
- ◆Over-range indication
- ◆Max/Min
- ◆Data hold





深圳市福禄思科技有限公司
SHENZHEN FLUS TECHNOLOGY CO., LTD.
www.szflus.com

Specifications

Function \ Model	ET-952
Measuring Range	0~400k Lux, 0~ 40k Fc
Operating Conditions	-20~60°C; <90%RH(Non-condensation)
Storage Conditions	-20~60°C; <75%RH
Accuracy	±3% rdg±0.5%f.s.(<10,000Lux) ±4% rdg±10dgts.(>10,000Lux)
Sampling Rate	2 times/ second
Spectral Response	CIE photopic (CIE human eye response curve)
Over Range Indication	LCD displays "-OL-" or "-LO-"
Spectral Accuracy	CIE V λ function (f1'≤6%,f2'≤2%)
Photo Detector Lead Length	approx. 2.5m





Dimension(L*W*H): 185*66*33mm
Weight: 327g
Accessories: User's manual, 9Vbattery, photo detector, tripod（optional),carrying case, large gift box